

22.2 - Lunderquist viela-pavedēja

ACCESSORIES

GUIDE WIRES

STANDARD GUIDE WIRE



Standard – PTFE-coated stainless steel

Order Codes	Diameter (inch)	Length (cm)	Tip	Tip Stiffness	Shaft Stiffness
EN-340028	0.028"	100	straight	standard	standard
EN-340032	0.032"	100	straight	standard	standard
EN-340035	0.035"	100	straight	standard	standard
EN-340038	0.038"	100	straight	standard	standard
SU-120101	0.045"	100	straight	standard	standard
EN-340125	0.025"	125	straight	standard	standard
EN-340128	0.028"	125	straight	standard	standard
EN-340135	0.035"	125	straight	standard	standard
EN-340135-S	0.035"	125	straight	standard	stiff
EN-340228	0.028"	145	straight	standard	standard
EN-340150	0.035"	150	straight	standard	standard
EN-340035-J3	0.035"	100	J-tip (3.0 mm)	standard	standard

Lunderquist – PTFE-coated stainless steel - Lunderquist viela-pavedēja

Order Codes Kodas	Diameter (inch) vielos diam.	Length (cm) vielos ilgis	Tip Galiukas	Tip Stiffness	Shaft Stiffness veleno standumas
RE-420170	0.025"	70	straight	standard	stiff
RE-420780	0.035"	80	J-tip (1.5 mm)	standard	stiff
RE-420380	0.035"	80	J-tip (3.0 mm)	standard	stiff
RE-420180	0.035"	80	straight -tiesus	standard	stiff standus

With movable core – PTFE-coated stainless steel

Order Codes	Diameter (inch)	Length (cm)	Tip	Tip Stiffness	Shaft Stiffness
RE-420210	0.035"	125	straight	standard	standard
RE-420211	0.035"	150	straight	standard	standard

Schüller Guide wire – uncoated stainless steel

Order Codes	Diameter (inch)	Length (cm)	Tip 9 cm	Tip Stiffness	Shaft Stiffness
RE-430300	0.035"	100	J-tip (3.0 mm)	standard	stiff