Oliflex Heat125 SC 0,5mm2

UPS
Input Output

Power 24V (B+ signal)
(from Main switch)
Fuse 10A

GND

Fuse 5A

Ignition (+15 signal)

Driver Display

Holder

ETHERLINE® Y Flex
CAT.5e

On-Board Unit

WiFi antenna

Gooseneck
Microphone with holder and cap

GNSS/LTE antenna

Fuse 2,5A

CAT 5e SF-UTP patch
cord, Cu, PVC AWG 26/7

Unitronic
LiYCY 2x0,5

ÖPVC-JZ
3g0,75
EN
VCC
GND
Validator #1

Fuse 2,5A

Industrial Cat5e
2x4x26AWG, shielded

ÖPVC-JZ
3g0,75
EN
VCC
GND
Validator #2

Fuse 2,5A

Industrial Cat5e
2x4x26AWG, shielded

ÖPVC-JZ
3g0,75
EN
VCC
GND
Validator #3

Fuse 2,5A

Industrial Cat5e
2x4x26AWG, shielded

ÖPVC-JZ
3g0,75
EN
VCC
GND
Validator #4

Fuse 2,5A

Industrial Cat5e
2x4x26AWG, shielded

Ethernet switch

Buses PA system

RIDANGO

Vilnius connection scheme

SIZE	FSCM NO		DWG NO		REV
SCALE	NA			SHEET	1 OF 1