

**Marathon M FT**  
constant current discharge

5 Vpc - Discharge in A at 20 °C

| Type     | Part number      | 3 min | 5 min | 10 min | 15 min | 30 min | 1 h  | 1.5 h | 2 h  | 3 h  | 5 h  | 8 h  | 10 h | 12 h | 24 h |
|----------|------------------|-------|-------|--------|--------|--------|------|-------|------|------|------|------|------|------|------|
| M2V200FT | NAMT060200HMOMFA | 640   | 560   | 435    | 357    | 231    | 139  | 99.8  | 78.6 | 56.3 | 36.9 | 25.0 | 20.5 | 17.3 | 9.14 |
| M2V35FT  | NAMF120035HMOMFA | 75.5  | 75.5  | 75.5   | 75.5   | 45.0   | 26.9 | 18.7  | 14.5 | 10.3 | 6.75 | 4.40 | 3.59 | 3.04 | 1.62 |
| M2V50FT  | NAMF120050HMOMFA | 264   | 199   | 129    | 95.0   | 53.5   | 29.6 | 24.7  | 19.3 | 13.8 | 9.08 | 5.92 | 4.80 | 4.04 | 2.11 |
| M2V60FT  | NAMF120060HMOMFA | 295   | 232   | 147    | 111    | 65.5   | 40.8 | 29.4  | 23.3 | 16.8 | 11.1 | 7.49 | 6.09 | 5.13 | 2.69 |
| M2V90FT  | NAMF120090HMOMFA | 390   | 315   | 215    | 165    | 108    | 65.1 | 46.0  | 36.0 | 25.2 | 16.1 | 10.6 | 8.79 | 7.49 | 4.08 |
| M2V105FT | NAMF120105HMOMFA | 445   | 370   | 258    | 197    | 120    | 72.6 | 52.0  | 41.0 | 29.2 | 19.0 | 12.9 | 10.4 | 8.82 | 4.60 |
| M2V125FT | NAMF120125HMOMFA | 250   | 250   | 250    | 250    | 152    | 91.2 | 65.7  | 52.0 | 37.7 | 24.0 | 15.6 | 12.7 | 10.8 | 5.75 |
| M2V155FT | NAMF120155HMOMFA | 555   | 470   | 340    | 274    | 180    | 106  | 78.0  | 62.5 | 44.4 | 28.6 | 19.2 | 15.6 | 13.1 | 6.88 |

60 Vpc - Discharge in A at 20 °C

| Type     | Part number      | 3 min | 5 min | 10 min | 15 min | 30 min | 1 h  | 1.5 h | 2 h  | 3 h  | 5 h  | 8 h  | 10 h | 12 h | 24 h |
|----------|------------------|-------|-------|--------|--------|--------|------|-------|------|------|------|------|------|------|------|
| M6V200FT | NAMT060200HMOMFA | 680   | 590   | 450    | 365    | 233    | 139  | 99.7  | 78.6 | 56.3 | 36.9 | 25.0 | 20.5 | 17.3 | 9.14 |
| M2V35FT  | NAMF120035HMOMFA | 75.5  | 75.5  | 75.5   | 75.5   | 45.0   | 26.9 | 18.7  | 14.5 | 10.3 | 6.75 | 4.40 | 3.59 | 3.04 | 1.62 |
| M2V50FT  | NAMF120050HMOMFA | 270   | 202   | 131    | 97.0   | 54.0   | 30.0 | 24.7  | 19.3 | 13.8 | 9.08 | 5.92 | 4.80 | 4.04 | 2.11 |
| M2V60FT  | NAMF120060HMOMFA | 305   | 240   | 150    | 112    | 66.0   | 40.8 | 29.4  | 23.3 | 16.8 | 11.1 | 7.49 | 6.09 | 5.13 | 2.69 |
| M2V90FT  | NAMF120090HMOMFA | 400   | 330   | 220    | 170    | 110    | 65.1 | 46.0  | 36.0 | 25.2 | 16.1 | 10.6 | 8.79 | 7.49 | 4.08 |
| M2V105FT | NAMF120105HMOMFA | 460   | 380   | 260    | 201    | 122    | 73.4 | 52.0  | 41.0 | 29.2 | 19.0 | 12.9 | 10.4 | 8.82 | 4.60 |
| M2V125FT | NAMF120125HMOMFA | 250   | 250   | 250    | 250    | 152    | 91.2 | 65.7  | 52.0 | 37.7 | 24.0 | 15.6 | 12.7 | 10.8 | 5.75 |
| M2V155FT | NAMF120155HMOMFA | 600   | 495   | 350    | 277    | 181    | 106  | 78.0  | 62.5 | 44.4 | 28.6 | 19.2 | 15.6 | 13.1 | 6.88 |

Discharge data are also valid for other terminals/containers.

17