



Marathon M FT  
Constant power discharge

1 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M6V200FT	NAMT060200HM0FA	1030	1030	1030	1030	804	551	416	341	247	164	112	91.9	77.8	41.3
M2V35FT	NAMF120035HM0MA	564	564	564	564	377	231	165	130	92.5	59.8	40.0	33.0	28.3	15.6
M2V50FT	NAMF120050HM0MA	731	731	731	731	492	311	232	184	129	82.5	54.6	44.9	38.3	20.8
M2V60FT	NAMF120060HM0MA	882	882	882	882	597	365	265	211	153	102	67.5	55.0	46.6	24.6
M2V90FT	NAMF120090HM0FA	1180	1180	1180	1180	870	562	407	324	235	156	103	84.5	71.5	37.9
M2V105FT	NAMF120105HM0FA	1250	1250	1250	1250	968	612	443	352	255	170	112	91.8	78.0	41.9
M2V125FT	NAMF120125HM0FA	1159	1159	1159	1159	729	533	427	312	210	146	118	118	99.7	51.8
M2V155FT	NAMF120155HM0FA	1337	1337	1337	1337	862	649	530	385	257	174	142	121	121	64.6
M2V180FT	NAMF120180VM0FA	1454	1454	1454	1454	1454	997	718	570	417	277	190	159	138	79.2

92 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M6V200FT	NAMT060200HM0FA	1110	1110	1110	1110	857	585	443	363	262	173	118	96.9	82.1	43.8
M2V35FT	NAMF120035HM0MA	601	601	601	601	399	247	176	139	98.3	63.4	42.4	35.0	29.9	16.5
M2V50FT	NAMF120050HM0MA	798	798	798	798	525	331	245	196	137	87.4	57.7	47.4	40.3	21.9
M2V60FT	NAMF120060HM0MA	1017	1017	1017	1017	644	392	283	224	162	107	71.8	58.5	49.4	26.1
M2V90FT	NAMF120090HM0FA	1290	1290	1290	1290	944	596	430	342	247	164	109	88.9	75.2	39.8
M2V105FT	NAMF120105HM0FA	1526	1526	1526	1526	1025	651	470	373	269	180	118	97.0	82.4	44.2
M2V125FT	NAMF120125HM0FA	1237	1237	1237	1237	778	567	458	330	222	155	125	105	105	54.8
M2V155FT	NAMF120155HM0FA	1626	1626	1626	1626	1407	916	684	556	403	269	184	150	127	67.9
M2V180FT	NAMF120180VM0FA	1554	1554	1554	1554	1554	1052	771	610	444	293	200	167	144	82.1

1.90 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M6V200FT	NAMT060200HM0FA	1200	1200	1200	1200	920	620	470	386	277	182	125	102	86.6	46.0
M2V35FT	NAMF120035HM0MA	641	641	641	641	422	262	187	147	104	67.0	44.7	36.9	31.6	17.4
M2V50FT	NAMF120050HM0MA	868	868	868	868	561	351	259	208	145	92.3	60.8	49.9	42.4	22.9
M2V60FT	NAMF120060HM0MA	1114	1114	1114	1114	694	420	301	238	171	112	76.1	61.9	52.3	27.6
M2V90FT	NAMF120090HM0FA	1360	1360	1360	1360	990	630	454	359	259	171	114	93.4	78.9	41.6
M2V105FT	NAMF120105HM0FA	1600	1600	1600	1600	1085	690	497	393	283	187	125	102	86.8	46.4
M2V125FT	NAMF120125HM0FA	1321	1321	1321	1321	828	601	479	348	233	164	133	111	111	57.8
M2V155FT	NAMF120155HM0FA	1916	1916	1916	1916	1517	975	718	579	419	282	195	159	134	71.2
M2V180FT	NAMF120180VM0FA	1648	1648	1648	1648	1648	1102	819	646	468	308	209	174	150	85.0

1.87 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M6V200FT	NAMT060200HM0FA	1320	1320	1320	1320	1006	664	502	411	294	193	130	107	91.2	48.4
M2V35FT	NAMF120035HM0MA	679	679	679	679	444	277	198	155	109	70.5	46.9	38.7	33.0	18.1
M2V50FT	NAMF120050HM0MA	939	939	939	939	596	371	270	214	152	96.7	63.5	52.0	44.2	23.7
M2V60FT	NAMF120060HM0MA	1130	1130	1130	1130	740	444	318	251	180	118	79.8	64.9	54.8	28.9
M2V90FT	NAMF120090HM0FA	1430	1430	1430	1430	1035	665	477	377	271	178	119	97.6	82.4	43.4
M2V105FT	NAMF120105HM0FA	1670	1670	1670	1670	1144	722	519	410	295	194	130	106	90.5	48.3
M2V125FT	NAMF120125HM0FA	1400	1400	1400	1400	1400	873	634	504	366	244	168	139	117	60.6
M2V155FT	NAMF120155HM0FA	2200	2200	2200	2200	1634	1042	758	605	440	295	203	165	140	74.1
M2V180FT	NAMF120180VM0FA	2980	2980	2980	2980	2549	1765	1164	875	688	496	324	219	182	87.9