

Marathon M FT
Constant power discharge

5 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M200FT	NAMT06200HM0FA	1920	1820	1600	1420	1060	692	522	427	305	199	134	111	94.0	49.8
M235FT	NAMF120035HM0MA	710	710	710	710	460	288	205	161	113	72.8	48.4	39.9	34.0	18.6
M250FT	NAMF120050HM0MA	988	988	988	988	620	387	276	217	155	101	66.0	53.6	45.3	23.8
M260FT	NAMF120060HM0MA	1174	1174	1174	1174	786	449	324	257	185	122	82.3	66.9	56.5	29.7
M290FT	NAMF120090HM0FA	2280	2080	1730	1480	1060	689	493	389	279	183	123	100	84.8	44.6
M2105FT	NAMF120105HM0FA	2989	2700	2090	1720	1185	743	533	422	303	199	134	109	93.0	49.6
M2125FT	NAMF120125HM0FA	2114	2114	2114	2114	1454	905	655	521	377	251	172	144	121	62.4
M2155FT	NAMF120155HM0FA	3500	3200	2700	2350	1717	1083	786	626	454	303	209	170	143	75.9
M2180FT	NAMF120180VM0FA	3168	3168	3168	3168	2659	1832	1196	894	709	510	332	224	185	89.1

83 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M6200FT	NAMT06200HM0FA	2070	1950	1700	1500	1100	712	535	437	311	203	138	112	95.3	50.6
M21235FT	NAMF120035HM0MA	730	730	730	730	468	292	208	163	115	73.8	49.1	40.4	34.5	18.9
M21260FT	NAMF120060HM0MA	1014	1014	1014	1014	633	396	281	221	157	102	67.2	54.5	45.8	23.8
M21290FT	NAMF120090HM0FA	2430	2200	1820	1550	1090	700	501	395	282	185	124	101	85.8	45.2
M21105FT	NAMF120105HM0FA	3121	2810	2200	1800	1216	760	545	431	309	203	137	112	95.0	50.3
M21125FT	NAMF120125HM0FA	2178	2178	2178	2178	1489	924	669	532	385	256	176	148	124	63.4
M21155FT	NAMF120155HM0FA	3850	3400	2850	2450	1770	1112	805	641	464	309	213	173	146	77.3
M21180FT	NAMF120180VM0FA	3344	3344	3344	3344	2763	1889	1224	917	726	520	338	227	188	161

1.80 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M6200FT	NAMT06200HM0FA	2327	2160	1840	1605	1165	749	558	453	322	209	142	116	98.2	51.9
M21235FT	NAMF120035HM0MA	762	762	762	762	481	299	213	167	117	75.4	50.1	41.3	35.2	19.2
M21260FT	NAMF120060HM0MA	1055	1055	1055	1055	653	407	289	227	161	104	68.8	55.5	46.6	23.9
M21290FT	NAMF120090HM0FA	2600	2330	1890	1600	1110	717	512	403	288	192	127	85.5	58.6	30.7
M21105FT	NAMF120105HM0FA	3313	2950	2250	1840	1249	780	558	441	316	207	140	114	96.9	51.2
M21125FT	NAMF120125HM0FA	2255	2255	2255	2255	1532	949	686	545	394	262	179	151	127	64.8
M21155FT	NAMF120155HM0FA	4100	3650	3000	2530	1820	1148	829	658	475	316	217	177	149	78.8
M21180FT	NAMF120180VM0FA	3589	3589	3589	3589	2905	1958	1254	938	743	531	344	231	191	163

1.78 Vpc - Discharge in W/block at 20 °C

Type	Part number	3 min	5 min	10 min	15 min	30 min	1 h	1.5 h	2 h	3 h	5 h	8 h	10 h	12 h	24 h
M6200FT	NAMT06200HM0FA	2460	2270	1910	1660	1193	760	565	457	325	211	143	117	98.9	52.2
M21235FT	NAMF120035HM0MA	773	773	773	773	485	301	214	168	118	76.0	50.5	41.6	35.5	19.4
M21260FT	NAMF120060HM0MA	1059	1059	1059	1059	658	409	290	228	162	105	69.1	55.7	46.8	24.0
M21290FT	NAMF120090HM0FA	2910	2570	2000	1650	1130	721	514	404	290	189	128	104	87.9	46.3
M21105FT	NAMF120105HM0FA	3456	3070	2350	1900	1272	789	565	446	319	210	142	115	98.0	51.7
M21125FT	NAMF120125HM0FA	2291	2291	2291	2291	1552	960	694	551	398	264	181	153	128	65.6
M21155FT	NAMF120155HM0FA	4350	3900	3120	2600	1860	1166	841	668	482	320	220	179	151	79.6
M21180FT	NAMF120180VM0FA	3692	3692	3692	3692	2988	1994	1269	945	751	536	347	232	192	164