



TECHNICAL DATA SHEET

P0763ST

ITEM: **PLASTIWAX**

TYPE	Packaging	Melting point	Packaging for sale	Characteristics
PLASTIWAX REF 0763 REF 0864	Kg. 2,5 Kg. 1	54-57 °C	4 x 2,5 Kg. 10 x 1 Kg.	Suitable for embedding of fragile tissues that are not easily dissected as fibroid tumors, tissues covered in blood, thrombus, decalcified bones and cartilage. No chipping.
PLASTIWAX PLUS REF 0764	Kg,2,5	54-57 °C	4 x 2,5 Kg.	Added with special polymer that enhances infiltration into tissues.

MANUFACTURER: KALTEK srl

CND: W05030599

- Mixture of pure paraffin and plastic polymers for embedding of hard and soft histological tissues.
- The drop-shaped **PlastiWax** allows a rapid melting.
- Twice filtered – it doesn't need to be filtered before use.
- 2,5 Kg disposable packaging, it is easy to handle and resealable with Minigrip system.
- It does not contain DMSO
- Shelf life: 5 years

WARNING

- Do not heat over 62 °C;
- Store maximum at 36 °C;
- Avoid direct sun's rays exposition;
- The product can be used even if there has been a **PlastiWax** drops aggregation in the container. Beat the closed container on a smooth surface in order to obtain adequate drops.

CONFORMITY

PlastiWax complies with the following norms and directives:

- 98/79/ED Directive of 27/10/1998 (IVD)
- UNI CEI EN ISO 14971:2009
- UNI CEI EN 15223-1:2012



REF 0864



REF 0763



REF 0764