

August 28, 2023

TO WHOM IT MAY CONCERN

This is a letter to confirm that:

- 3.1 Distal Dorsal Humeral locking compression plates 2.7/3.5, catalog numbers 22594103 – 22594209, are limited contact, used with 2.7 mm locking, 3.5 mm cortex and 3.5 mm locking screws.
 - 3.2 Distal Medial Humeral locking compression plates 2.7/3.5, catalog numbers 22579106 – 22579212, are limited contact, used with 2.7 mm locking, 3.5 mm cortex and 3.5 mm locking screws.
 - 3.3 Distal Radius Volar locking compression plate, catalog numbers 29568300 – 29568402, used with 2.7 mm locking, 3.5 mm cortex and 2.0 mm Smooth screws. There are 7 holes for 2.7 mm locking screws at the distal end of the plate.
 - 3.8 Locking L plate 2.7, catalog numbers 24209100, 24209200, 90 degrees. Used with 2.7 mm locking and 2.7 mm cortex screws.
 - 3.9 Locking L plate 2.7, oblique, catalog numbers 24210100, 24210200, 106 degrees. Used with 2.7 mm locking and 2.7 mm cortex screws.
 - 3.14 Anterolateral Clavicular Locking Compression plates, catalog numbers 22578110-22578215, used with 2.7 mm locking, 3.5 mm locking and 3.5 mm cortex screws. There are 7 holes for 2.7 mm locking screws at the lateral end of the plate.
 - 3.16 Locking compression plates 3.5, catalog numbers 22501004-22501012 are limited contact, used with 3.5 mm locking and 3.5 mm cortex screws.
 - 3.17 Straight Locking Compression plates 3.5, catalog numbers 22596004 – 22596012. are limited contact
-
- 6.1 4.0 mm diameter cannulated cancellous screws, partially threaded, catalog numbers 31421025 - 31421070 are self-tapping, made of titanium alloy. Screws are self-tapping both ways.
 - 6.3 4.5 mm diameter cannulated cancellous screws, partially threaded, catalog numbers 31405020 - 31405075 are self-drilling, self-tapping, made of titanium alloy. Screws are self-tapping both ways.
 - 6.6 Guide wire diam. 1.6 mm, catalog number 236111, length is 150 mm.
 - 6.7 Threaded pin diam. 1.6 mm, catalog number 236121, length is 150 mm.
 - 6.8 7.3 mm diameter cannulated cancellous screws, 16 mm thread, catalog numbers 31401040 - 31401096 are self-drilling, self-tapping, made of titanium alloy. Screws are self-tapping both ways.
 - 7.3 mm diameter cannulated cancellous screws, 32 mm thread, catalog numbers 31404050 - 31404096 are self-drilling, self-tapping, made of titanium alloy. Screws are self-tapping both ways.
 - 6.11 Guide wire diam. 2.5 mm, catalog number 241250, length is 250 mm.
 - 6.12 Threaded pin diam. 2.5 mm, catalog number 241260, length is 250 mm.

In Kanghui Trauma Catalog, PT means “pure titanium”, TA means “titanium alloy”.