



Hydraulic breaker

MH




Technical Specification



Silenced hydraulic breaker with fully enclosed body.
High back pressure is taken in the return line to ease

operation on skid loaders, mini excavators and back-hoe loaders with no stop.

Hydraulic breaker

MODEL		MH 60 S	MH 100 S	MH 180 S	MH 250 S	MH 300 S	MH 350 S	MH350BL	MH 420 S	MH 550 S	
Oil flow, min-max	lt/min	15-20	20-40	30-50	40-60	45-85	55-80	55-80	70-90	80-110	
Oil pressure, min-max	bar	130-150			90-120			90-130			
Weight standard configuration	kg	60	100	180	250	280	350	380	420	550	
Tool	Ø mm	36	48	54	68	72	78		82		
Back pressure	bar	25	30	25			30				
Energy per stroke	joule	100-122	150-230	240-360	450-600	450-600	600-820	650-850	680-900	650-1000	
Strokes per minute		1000-1350		800-1200	650-950	700-1000	600-900	650-750	650-850	700-950	
	ton	-	1,3-1,8	2,0-2,6	2,6-3,7	3,5-4,0	3,7-4,8	-	4,0-5,5	-	
Backhoe 	ton	-	2,4-3,2	3,2-5,0	5,0-7,0	6,0-8,0	7,0-9,0	7,0-9,0	8,0-10,0	9,0-12,0	
	ton	0,8-1,2	1,2-2,2	2,2-3,2	3,2-4,5	3,5-5,0	4,5-8,0		7,0-9,0	8,0-11,0	
	Overall size in standard configuration	A cm	23	26	33	36	40	41	60	45	48
		B cm	65	80	97	109	115	121	150	130	147
		C cm	23	26	33	36	40	41	60	55	50

