

Piston compressor, mobile, low noise
SilentMaster
SEM 30-8-4 W
Art.-Nr. A 333 005



Technical data



Intake capacity:	30 l/min
Filling capacity:	19 l/min
Pressure:	8 bar
Tension:	230 V~ 50 Hz
Engine power:	0,2 kW
Engine speed:	2900 min/1
Sound pressure level:	31 dB(A)
Container volume:	4 l
Air outlet connection:	quick coupling
Dimensions (WxDxH):	425x195x430 mm
Weight:	19 Kg
Stand:	18.06.2007 / wsmi

General description

Construction

Portable compressor in a compact design, standard with all safety fittings and electrical connection cable with plug.

Pressure switch with
Start-up relief

The pressure switch with on/off switch and start-up relief enables automatic operation. Once the maximum pressure of 8 bar is reached, the compressor switches off automatically. If the pressure drops by approximately 2 bar due to air withdrawal, it restarts automatically. The start-up relief ensures a smooth, load-free start-up.

equipment

The compressor is equipped with a pressure regulator, a pressure gauge, and a quick-release coupling. The pressure regulator allows you to set the desired working pressure and provides air that is clean of condensate, dirt, and oil. The quick-release coupling makes connecting tools easier.

use

Thanks to the special sound insulation, the compressor operates almost silently and is therefore ideally suited for use directly at the workplace.
Ideally suited for airbrush work.

Scope of delivery

An instruction manual and the container inspection documents.

Guarantee

- 24 months for exclusively private use
- 12 months for commercial/professional use

Piston compressor, mobile, low noise
SilentMaster
SEM 30-8-4 W
Art.-Nr. A 333 005



Compressor

- | | |
|-----------------------------|--|
| 1-cylinder unit | The single-cylinder engine operates extremely quietly. |
| Directly flanged unit | The directly flanged unit eliminates the need for an intermediate gearbox and the associated wear and tear. Virtually lossless power transmission between the motor and compressor saves energy. |
| Motor protection switch | The built-in motor protection prevents damage in case of overload or incorrect operation. |
| AC power connection
230V | Simplifies connection. Enables operation on a standard AC power grid.

Good start-up properties. |

container

- | | |
|--------------------------------------|--|
| equipment | The compressed air tank is equipped with a safety valve, tank pressure gauge and condensate drain valve. |
| Warranty against
Rust perforation | The container comes with a 10-year warranty against rust perforation. |

Technical details, equipment options, and illustrations may differ from the descriptions. Therefore, we reserve the right to change the data published here.