



MENU

EN



PIEZON® 150

Technical specifications

Equipment

# PIEZON® 150



## TECHNICAL DATA:

|                          |   |
|--------------------------|---|
| Manufacturer             | EMS SA, CH-1260 Nyon, Switzerland                                     |
| Model                    | PIEZON® 150   |
| Classification           |   |
| EN 60601-1               | Class II<br>Applied part, Type BF<br>IP 20, unit<br>IP X1, foot pedal |
| 93/42/EEC                | Class IIa   |
| Operating mode           |   |
| with irrigation          | Continuous operation  |
| without irrigation       | Duty cycle 10% during 10 min. maximum                                 |
| Power                    |   |
| Supply voltage           | 100-240 VAC 50/60Hz   |
| Ultrasound specification |   |
| Maximum output           | 8 Watts   |
| Frequenz Range (min)     | 24 kHz  |
| Frequenz Range (max)     | 32 kHz  |
| Dimensions & weight      |   |
| Width                    | 170 mm  |
| Depth                    | 135 mm  |

Height

96 mm

Weight (approx.)

0.6 kg

Operating conditions

+10 °C to +40 °C  
30% to 75% relative humidity

Storage and transport conditions

-10 °C to +40 °C  
10% to 95% relative humidity  
500 hPa to 1060 hPa air pressure



PIEZON® 150



English

TESTIMONIALS

GUIDED BIOFILM  
THERAPY

PRODUCTS

TABLE TOPS

HANDYS

ACCESSORIES

POWDERS

SWISS INSTRUMENTS™

BUILT-IN KITS

PIEZON® SURGERY

MEDIA

MEDIA  
CENTER

NEWSROOM

ABOUT EMS

OVERVIEW

MISSION AND  
VALUES

HISTORY

CAREER

ENVIRONMENTAL  
PROTECTION

CONTACT

SWISS DENTAL  
ACADEMY

MY EMS

IMPRESSUM

DATA PRIVACY

COOKIE POLICY

LEGAL NOTICE



© 2018 EMS