



MENU

EN



PIEZON® 250

Technical specifications

Equipment

PIEZON® 250



TECHNICAL DATA:

Manufacturer	EMS SA, CH-1260 Nyon, Switzerland
Model	PIEZON® 250
Classification	
EN 60601-1	Class II Applied part, Type BF IP 20, unit IP X1, foot pedal
93/42/EEC	Class IIa
Operating mode	
with irrigation	Continuous operation
without irrigation	Duty cycle 10% during 10 min. maximum
Power	
Supply voltage	100-240 VAC 50/60Hz
Ultrasound specification	
Maximum output	8 Watts
Frequenz Range (min)	24 kHz
Frequenz Range (max)	32 kHz
Dimensions & weight	
Width	153 mm
Depth	215 mm

Height 96 mm

Weight (approx.) 1 kg

Operating conditions +10 °C to +40 °C
30% to 75% relative humidity

Storage and transport conditions -10 °C to +40 °C
10% to 95% relative humidity
500 hPa to 1060 hPa air pressure



PIEZON® 250

English

TESTIMONIALS

GUIDED BIOFILM THERAPY

PRODUCTS

TABLE TOPS

HANDYS

ACCESSORIES

POWDERS

SWISS INSTRUMENTS™

BUILT-IN KITS

PIEZON® SURGERY

MEDIA

MEDIA CENTER

NEWSROOM

ABOUT EMS

OVERVIEW

MISSION AND VALUES

HISTORY

CAREER

ENVIRONMENTAL PROTECTION

CONTACT

SWISS DENTAL ACADEMY

MY EMS

IMPRESSUM

DATA PRIVACY

COOKIE POLICY

LEGAL NOTICE



© 2018 EMS