

# Dynamic Duo

## Dual hoppers. Singular solution.

Introducing the **SlideMate Pro thermal transfer microscope slide printer from Epreidia**, a smart solution with flexible configuration options to match your laboratory's needs.

Avoid the annoyance and wasted time caused by constantly loading and unloading your laboratory's slide printer to switch between multiple slide types. The SlideMate Pro printer features a dual-hopper loading system with intelligent slide selection. Load adhesion slides in one hopper, non-adhesion slides in the other – the printer can be programmed to automatically read the requested slide type from the incoming print image and pull from the appropriate hopper.

Have a need for one-off or specialty slides? Simply load them through the manual feed as required – no need to remove the hoppers.

Want to maximise throughput? Load matching slides in both hoppers and enjoy the benefits of quick printing times.

Setup is simple. The new SlideMate Pro software uses a Windows®-based driver that easily connects to other computers and laboratory information systems. SlideMate Pro enables sample-tracking solutions including user log-in information, time and date stamp on each slide, and unique transaction IDs.

For more information, contact your local Epreidia Territory Account Manager or visit [epredia.com](https://www.epredia.com)



## SlideMate Pro

### Microscope Slide Printer

- Efficient performance: dual-hopper design with intelligent slide selection
- High throughput: 4-5 seconds per slide
- Simple integration: Windows-based driver and Gateway functions

#### Ordering Information

|                         |           |
|-------------------------|-----------|
| SlideMate Pro printer   | A83900015 |
| Spare hopper            | A83910011 |
| Thermal transfer ribbon | A83910001 |
| Head cleaning kit       | A83910008 |

#### Product Specifications

|                           |  |
|---------------------------|--|
| Dimensions (DxWxH)        | 330 x 163 x 406 mm<br>13 x 6.4 x 16 in       |
| Power requirements        | Universal 100-240 VAC<br>50-60 Hz, 1.2A max. |
| Slide type                | 25 x 75 x 1 mm, 1 x 3 in                     |
| Print speed               | 4-5 seconds per slide                        |
| Media type                | Thermal transfer ribbon                      |
| Media capacity            | 1 roll, ~12,000 slides per roll              |
| Media colour / Resolution | Black / 300 dpi                              |
| Connectivity              | Ethernet, USB-A (2), USB-B (1)               |

